

SPECIFICATIONS

Task	Capacity Load	Internal Size L x W x H Inches Centimeters	External Size L x W x H Inches Centimeters	Weight Lb. Approx.	Freq. Hz Approx.	Max. r.m.f. dB(A) Power Level	Connected Load (VA)	Powering Input Watt	Heating Adjustable Non-adjustable	Ball wheel
P100 L	0.80	7 1/8 x 7 18 x 17.5 x 6	8 1/4 x 8 21.5 x 18 x 15.5	1.8	45	80/10	60	none		
P100 S 1/8	0.80	7 1/8 x 7 18 x 17.5 x 6	8 1/4 x 8 21.5 x 18 x 15.5	1.8	45	80/10	120	40	Non-adjustable 80%	
P100 L	1.75	8 1/2 x 8 144 x 18.4 x 10	7 1/8 x 11 17.5 x 18.5 x 20	1.7	45	120/180	100	none		
P100 S 1/8	1.75	8 1/2 x 8 144 x 18.4 x 10	7 1/8 x 11 17.5 x 18.5 x 20	1.7	45	120/180	230	120	Adjustable 80%	
P100 S	2.75	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 8 26.0 x 16.1 x 11.9	1.7	45	180/180	120	none		
P100 S 1/8	2.75	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 8 26.0 x 16.1 x 11.9	1.7	45	180/180	360	240	Adjustable 80%	
P100 D	2.75	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 8 26.0 x 16.1 x 11.9	1.7	45	180/180	300	240	Adjustable 80%	
P100 D 1/8HF	2.75	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 8 26.0 x 16.1 x 11.9	1.7	100	180/180	360	240	Adjustable 80%	
P100 S	3.80	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 12 26.0 x 16.1 x 29.5	4.6	45	200/100	180	none		
P100 S 1/8	3.80	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 12 26.0 x 16.1 x 29.5	4.6	45	200/100	420	240	Adjustable 80%	
P100 D	3.80	9 1/2 x 8 24 x 17.7 x 10	10 1/8 x 12 26.0 x 16.1 x 29.5	4.6	45	200/100	420	240	Adjustable 80%	
P100 S	3.80	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 12 11.9 x 11.6 x 29.5	3.8	45	260/130	210	none		
P100 S 1/8	3.80	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 12 11.9 x 11.6 x 29.5	3.8	45	260/130	450	240	Adjustable 80%	
P100 D	3.80	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 12 11.9 x 11.6 x 29.5	3.8	45	260/130	450	240	Adjustable 80%	
P100 D 1/8HF	3.80	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 12 11.9 x 11.6 x 29.5	3.8	100	260/130	490	240	Adjustable 80%	
P1100 L 1/8	11.00	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 10 11.9 x 10.5 x 11.5	10	45	400/200	1450	800	Adjustable 80%	yes
P1100 D	11.00	12 1/8 x 8 18 x 17.1 x 10	11 1/8 x 10 11.9 x 10.5 x 11.5	10	45	400/200	1650	800	Adjustable 80%	yes
P1200 L 1/8	11.00	19 1/8 x 8 49.5 x 19 x 10	20 1/8 x 10 51.5 x 19 x 17	9.5	45	400/200	1450	800	Adjustable 80%	yes
P1200 D	11.00	19 1/8 x 8 49.5 x 19 x 10	20 1/8 x 10 51.5 x 19 x 17	9.5	45	400/200	1650	800	Adjustable 80%	yes
P1500 L 1/8	15.00	13 1/8 x 12 32.7 x 30 x 29	14 1/8 x 10 35.2 x 25.5 x 11.5	11	45	480/240	1600	1200	Adjustable 80%	yes
P1500 D	15.00	13 1/8 x 12 32.7 x 30 x 29	14 1/8 x 10 35.2 x 25.5 x 11.5	11	45	480/240	1800	1200	Adjustable 80%	yes
P1800 L 1/8	22.00	20 1/8 x 12 50.5 x 30 x 15	21 1/8 x 14 53 x 32.5 x 36.5	24	45	480/240	1200	800	Adjustable 80%	yes
P1800 D	22.00	20 1/8 x 12 50.5 x 30 x 15	21 1/8 x 14 53 x 32.5 x 36.5	24	45	480/240	1200	800	Adjustable 80%	yes
P2000 L 1/8	29.50	20 1/8 x 12 50.5 x 30 x 29	21 1/8 x 14 53 x 32.5 x 36.5	24	45	640/320	2800	1800	Adjustable 80%	yes
P2000 D	29.50	20 1/8 x 12 50.5 x 30 x 29	21 1/8 x 14 53 x 32.5 x 36.5	24	45	640/320	2800	1800	Adjustable 80%	yes

L = Model with mechanical time

L 1/8 = Model with adjustable thermostat controlling up to approx. 80%

D = Model with digital control

D 1/8HF = Type D model with ultrasonic frequency approx. 132 kHz